

## Maintenance Instructions

MCLAREN DOORS have been engineered with our clients in mind. Our doors are designed to be virtually maintenance free to provide years of uninterrupted service. The unique integral hinge system and stainless steel rollers mean no rust and require no lubrication or greasing. The PVC door panels do not rust or delaminate ensuring the door looks great for years. Our doors are easily cleaned with a soap and water using a power washer.

MCLAREN DOORS can help reduce fleet operating costs and improve productivity. As MCLAREN DOORS require little or no maintenance, the savings in maintenance costs and lost productivity due to down time could amount to several hundred dollars over the life of the door, effectively paying for the door.

### Regular Maintenance:

- Keep the door clean. Wash regularly. In very dirty winter conditions you should also periodically clean the area between the panels (integral panel hinges) to remove grime from the panel hinge joints. (If significant grime is in the hinge joints you may need to pressure spray into the joints as the panels open at the top of the door)
- Do not lubricate the rollers, track or integral panel hinges as this will only attract dirt.
- Lubricate periodically (more often in refrigerated applications) with a dry spray lubricant: white lithium or a food grade lubricant:
  - Operator spring (such as white lithium or a food grade lubricant)
  - Operator shaft contact surfaces, studs on cable drums and the left cone winding of the spring, (ideally a penetrating lubricant)
- If you have a two point slam lock spray the end barrels regularly with a penetrating lubricant

